

TOWNHOMES IN RESIDENTIAL ZONING DISTRICTS

QUICK REFERENCE GUIDE

A Townhome is defined as a single-unit dwelling on its own lot or parcel, sharing a common side wall with another unit at the property line. The common wall must be fully enclosed and shared for at least 25% of the length of each dwelling unit's enclosed elevation, not including uncovered or open, covered porches, patios, decks or stoops. The common wall may be any wall of the dwelling unit, including the wall of an attached garage.

Common areas must be maintained by a homeowners association or other legal entity. A homeowners association may also be responsible for exterior building maintenance. A copy of any applicable covenants, restrictions and conditions must be recorded and provided to the City prior to issuance of a building permit.

See <u>Bend Development Code (BDC) 2.1</u> and <u>BDC 3.6.200.D</u> for detailed requirements.

This guide covers townhomes in residential zoning districts. For townhomes in Mixed Use zoning districts, refer to <u>BDC 2.3</u>.

ELIGIBILITY

Townhomes are permitted uses in the RL, RS, RM and RH zoning districts.

DEVELOPMENT STANDARDS

Lot Area and Dimension Requirements (see BDC 2.1.500)			
Zoning District	Minimum Lot Area	Minimum Lot Dimensions	
RL RS RM	Average minimum lot or parcel size: 1,500 sq. ft. for each unit	Minimum lot width: 20 ft.	
RH	Average minimum lot or parcel size: 1,200 sq. ft. for each unit	Minimum lot depth: 50 ft.	
All		Development alternatives: see <u>BDC Chapter 3.8</u>	

PLAN – Townhomes in Residential Zoning Districts



	• RL: 1.1
Minimum Density:	 RS: 4.0
Units/Gross Acre	• RM: 7.3

•	RH	:	21	.7

Maximum Density:	None	
	• RL: 35%	

Maximum Lot	 RS: 50% for single-story and 45% for all others
Coverage:	• RM: 60%
	RH: None

Duilding Cathooks	Coo DDC 2.4.200
Building Setbacks:	See BDC 2.1.300

	 RL and RS: 35 feet
Building Hoight	 RM: 40 feet

Building Height:

• RH: 50 feet

In the RS District, the FAR as defined in <u>BDC Chapter 1.2</u>, <u>Definitions</u>, must not exceed 1.1 for three-story residential uses and accessory structures.

Floor Area Ratio:

DESIGN STANDARDS SEE BDC 2.1.950

Garage Door Standards

The maximum combined garage door width facing the street is 50% of the total building width. The maximum combined garage door width facing the street may be up to 60% of the total building width if the front door entrance is within 10' of the longest street-facing wall of the dwelling unit. See Figure 2.1.950.

Exemptions:

- Existing garages legally constructed prior to November 5, 2021.
- When the side or rear wall of the garage faces the street, provided the standards of BDC 2.1.300(F)(1)(a) are met.

The entrance must either:

- Face the street;
- Be at an angle of up to 45 degrees from the street;

Front door Orientation Standards

- Face a common open space that abuts the street and is abutted by dwellings on at least two sides; or
- Open onto a porch. The porch must be at least 20 sq. ft. in area & have at least one entrance facing the street or have a roof. A covered walkway or breezeway is not a porch.

Exemptions to Orientation Standards.

Townhomes created by a conversion of an existing dwelling unit.

PLAN – Townhomes in Residential Zoning Districts



Accommodation Information for People with Disabilities

Page 2 of 4

Windows and Doors

A minimum of 15% of the area of all street facing facades must include windows and/or doors. Gabled areas and garage doors (in blue) and roofs (in white) are not included in the base wall calculation when determining the minimum 15% calculation for windows/door areas. Facades separated from the street property line by a dwelling are exempt from meeting this standard. See 2.1.950.D

PARKING

Alley Access

Minimum On-Site Spaces:	1 parking space per townhome
Minimum Dimensions	
If stall is at 90 degrees:	9 x 20 ft.
If stall is parallel:	9 x 22 ft.
Vehicle parking in a	9X18 ft.
dwelling unit's garage or	
carport	
For stalls at other angles	See <u>BDC 3.3.300.E.1</u>
Minimum Backup Distance	
Alley parking	24 ft.
Side entry garages	20 ft.

SITE IMPROVEMENTS (SEE BDC 4.2.400.A.3.B)

Proposed parking areas and driveways must be paved. Driveway apron design must conform to City of Bend Standards and Specifications. Townhomes may have a maximum of one driveway approach. Driveway access must be from the street with the lowest classification. The total width of shared driveway approaches must not exceed 32'. When a driveway serves more than one lot, the developer must record an access and maintenance easement/agreement to benefit each lot, prior to building permit issuance. Driveway approaches on local streets must be separated in compliance with the following: Approaches must be separated by a minimum of seven feet; and	Developments See BDC 3.6.200.D.2	Townhome developments and subdivisions (four or more lots) must receive vehicle access only from a rear alley, except when existing development patterns or topography make construction of an alley impractical.	
 Driveway access must be from the street with the lowest classification. The total width of shared driveway approaches must not exceed 32'. When a driveway serves more than one lot, the developer must record an access and maintenance easement/agreement to benefit each lot, prior to building permit issuance. Driveway approaches on local streets must be separated in compliance with the following: ▶ Approaches must be separated by a minimum of seven feet; and 			
Parking and Driveways: See BDC 3.6.200.D.3 ■ The total width of shared driveway approaches must not exceed 32'. When a driveway serves more than one lot, the developer must record an access and maintenance easement/agreement to benefit each lot, prior to building permit issuance. ■ Driveway approaches on local streets must be separated in compliance with the following: ➤ Approaches must be separated by a minimum of seven feet; and		 Townhomes may have a maximum of one driveway approach. 	
Driveways: See BDC 3.6.200.D.3 When a driveway serves more than one lot, the developer must record an access and maintenance easement/agreement to benefit each lot, prior to building permit issuance. Driveway approaches on local streets must be separated in compliance with the following: Approaches must be separated by a minimum of seven feet; and		 Driveway access must be from the street with the lowest classification. 	
Driveways: See BDC 3.6.200.D.3 an access and maintenance easement/agreement to benefit each lot, prior to building permit issuance. Driveway approaches on local streets must be separated in compliance with the following: Approaches must be separated by a minimum of seven feet; and	Parking and	, , , ,	
 See BDC 3.6.200.D.3 prior to building permit issuance. Driveway approaches on local streets must be separated in compliance with the following: ➤ Approaches must be separated by a minimum of seven feet; and 	Driveways:	·	
with the following: Approaches must be separated by a minimum of seven feet; and	See BDC	· · · · · · · · · · · · · · · · · · ·	
,,		, ,,	
Expension of a second common above the proportion are sufficient as 4.02		Approaches must be separated by a minimum of seven feet; and	
Except for snared approaches, the maximum width is 16.		Except for shared approaches, the maximum width is 16'.	
The minimum driveway width is 10'.		The minimum driveway width is 10'.	

PLAN - Townhomes in Residential Zoning Districts



Accommodation Information for People with Disabilities

Sidewalk and Curbs:	Sidewalks must be installed if sidewalks exist within 600 ft. of the property on the same side of the street; corner lots require ADA-compliant curb ramps.
Street and/or Alley Improvements:	Full street and/or alley improvements must be constructed along the property frontages when an improved street and/or alley has been built to the property line.
Water and Sewer Service:	Connections to the public sewer system are regulated by <u>Bend Code Title</u> <u>15</u> . (Consult a licensed plumber or professional designer/architect to determine if code requirements are met)
	A will-serve letter is required from the serving water district if property is not served by City of Bend water. (Call Avion at 541-382-5342 or Roats at 541-382-3029).

REQUIRED REVIEW PROCESS

- 1) A Minimum Development Standards Review application is not required; however, compliance with BDC 4.2.400.A.3, Approval Criteria is required and will be verified through the building permit process.
- 2) Register for and sign in to a CityView Portal account through the City of Bend's Online Permit Center
- 3) File for a <u>Building Permit</u> (Review time varies; anticipate 4-8 weeks)
- 4) Pay permit fees and System Development Charges (SDCs)
- 5) City issues Building Permit

Planning Division review may be required for structures on properties that are Historic Resources or located in the Historic Districts or Waterway Overlay Zone (WOZ). For more information, please contact planning@bendoregon.gov or 541-388-5580 menu option 3.

2020 FEES (EFFECTIVE JULY 1, 2021 - JUNE 30, 2022)

Building Permit	E-mail <u>building@bendoregon.gov</u> for estimate (Note: fee estimate includes SDCs)
System Development Charges (SDCs)	
For a townhome on previously undeveloped	\$4,394.00
property:	\$ 5,857.00 for 3/4" service; \$9,956.90 for 1"
Streets	\$5,223
Water (if served by City)	0 bedroom \$3,831
Sewer (if served by City)	1 bedroom \$4,221
Parks	2 bedroom \$6,845
	3+ bedroom \$8,867
For redevelopment or infill, SDC credits may apply.	• •

PLAN – Townhomes in Residential Zoning Districts



Accommodation Information for People with Disabilities